FG2000SX

10/100/Gigabit CardBus PC Card

The real 32-bit CardBus 10/100/1000M Gigabit Ethernet PC Card is here. The **Gigabit CardBus Card** gears with leading 32-bit bus architecture and full-duplex capability, which liberates an unmatched high-speed network performance. By providing smoothly connection to 10M bps, 100M bps and Gigabit Ethernet environments, the **Gigabit CardBus Card** is the ultimate solution for the CardBus equipped laptops. In addition, its auto-negotiation feature also configures to meet any kind of network connective modes.

Features

- PCMCIA CardBus standard compliant
- 32-bit bus-mastering data transfer
- 10M bps, 100M or 1000M bps data rates auto-negotiation
- Support Full Duplex flow control (IEEE 802.3x)
- Diagnostics LED indicators: 10 Link/Act, 100 Link/Act, 1000 Link/Act,
- Support both Category 3/5 (10BaseT) and Category 5e (100BaseTX/1000BaseT)
- IEEE 802 IP Layer 2 priority encoding
- Support all major Network Operating Systems (NOS)
- PC Card hot swap supported
- Ultra low power consumption

Downloaded from www.Manualslib.com manuals search engine

Specification

Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseTX IEEE 802.3ab for 1000BaseT PCMCIA CardBus PC Card standard
Port	1 x RJ 45 phone jack
Power consumption	695 mA (in operation) 600 mA (idle)
Temperature	Operating: 0~70 ℃ Storing: -10~70 ℃
Humidity	10%~85% (non-condensing, storage)
Supported OS	Windows 98SE, Windows 2000, Windows ME, Windows XP,
LED Indicators	10 / 100 / 1000 : Green LED
Physical Specification	Dimension : 107 (L)X 54 (W) X 8 (H) Weight : 45 g
Safety & Emission	FCC CE VCCI

Downloaded from www.Manualslib.com manuals search engine